

PRODUCT DATASHEET

Last information update: May 2023




ARKOS

0820W320

Architectural LED floodlight for outdoor applications

Technical Features

Power	320W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	16,000 lm ±10%
Light distribution type	symmetrical
Beam angle	ultra spot 2°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	36
MacAdam step	5
Power supply	Built-in
Control	ON/OFF
Protection index	IP66
Impact resistance	IK08
Lifetime	50,000 hours Ta=25°C



Construction

Fluorocarbonate powder painted die-cast aluminum body, tempered glass cover, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation


Surface mounted with adjustable base.

Finish Colours


RAL9023 as standard colour, other RAL colours on request.

Wiring

Power input cable OPEN END 500mm




Optional Accessories



built-in anti-glare accessory for improved visual comfort
*can not be ordered separately

honeycomb



anti-glare accessory for improved visual comfort
*can not be ordered separately

anti-glare glass



mounting accessory
*can not be ordered separately



U-bracket

Ordering Information

example: 0820W320.0002.2780.01+A1

0820W320 · [] · [] · [] + []

product	beam angle	light colour / CCT	finish colour	accessory
ARKOS 320W ULTRA SPOT	0002 2°	2780 2700K RA80	01 RAL9023	A1 honeycomb
		3080 3000K RA80		A2 anti-glare glass
		4080 4000K RA80		A3 U-bracket