

PRODUCT DATASHEET

Last information update: May 2023




HIGHLAND

0821W720

Architectural LED floodlight for outdoor applications


Technical Features

Power	720W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	32,400 lm ±10%
Light distribution type	symmetrical / elliptical
Beam angle	8°, 25° / 10°x45°
Light colour / CCT	RGBW
CRI	-
Source type	LED (4-IN-1)
LED number	80
MacAdam step	-
Power supply	Built-in
Control	DMX512
Protection index	IP66
Impact resistance	IK08
Lifetime	50,000 hours Ta=25°C



Wiring

Power input cable OPEN END 500mm
 DMX input cable MALE connector 500mm
 DMX output cable FEMALE connector 500mm



Construction

Fluorocarbonate powder painted die-cast aluminum body, tempered glass cover, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C


Installation

Surface mounted with adjustable bracket.

Finish Colours

RAL9023 as standard colour, other RAL colours on request.

Optional Accessories




built-in anti-glare accessory for improved visual comfort
*can not be ordered separately


honeycomb



anti-glare accessory for improved visual comfort
*can not be ordered separately




visor



with female 4-pin waterproof connector for DMX
* specify cable length to complete order

leader cable



with male and female 4-pin waterproof connector for DMX
* specify cable length to complete order

extension cable

Ordering Information

example: 0821W720.0008.4130K.01+A1

0821W720 · [] · [] · [] + []

product	beam angle	light colour / CCT	finish colour	accessory
HIGHLAND 720W	0008 8°	4130K RGB+3000K	01 RAL9023	A1 honeycomb
	0025 25°	4140K RGB+4000K		A2 visor
	1045 10°x45°			LC4 leader cable
				EC4 extension cable