

## PRODUCT DATASHEET

Last information update: May 2023




### ARC-SIDE

1915W10

Inground LED marker light for outdoor applications

#### Technical Features

Power	10W
Input voltage	DC24V ( constant voltage )
Insulation class	III
Delivered flux	600 lm ±10%
Light distribution type	symmetrical, 1-emission
Beam angle	5°, 15°, 30°, 60°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	1
MacAdam step	5
Power supply	Not included
Control	ON/OFF
Protection index	IP67
Impact resistance	IK10
Walk over	yes
Drive over	yes
Lifetime	50,000 hours Ta=25°C



#### Construction

Stainless steel body, engineering plastic recessed box, polycarbonate optical lenses.

#### Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

#### Installation

Ground recessed with recessed box.

#### Finish Colours

Stainless steel as standard colour. RAL colours on request.

#### Wiring

Power input cable OPEN END 500mm



## Ordering Information

example: 1915W10.0005.2780.01

1915W10 · [ ] · [ ] · [ ] + [ ]

product	beam angle	light colour / CCT	finish colour
ARC-SIDE 10W 1-EMISSION	<b>0005</b> 5°	<b>2780</b> 2700K RA80	<b>01</b> stainless steel
	<b>0015</b> 15°	<b>3080</b> 3000K RA80	
	<b>0030</b> 30°	<b>4080</b> 4000K RA80	
	<b>0060</b> 60°		

## PRODUCT DATASHEET

Last information update: May 2023




### ARC-SIDE

1915W10(220V)

Inground LED marker light for outdoor applications

#### Technical Features

Power	10W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	600 lm ±10%
Light distribution type	symmetrical, 1-emission
Beam angle	5°, 15°, 30°, 60°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	1
MacAdam step	5
Power supply	built-in
Control	ON/OFF
Protection index	IP67
Impact resistance	IK10
Walk over	yes
Drive over	yes
Lifetime	50,000 hours Ta=25°C



#### Construction

Stainless steel body, engineering plastic recessed box, polycarbonate optical lenses.

#### Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

#### Installation


Ground recessed with recessed box.

#### Finish Colours

Stainless steel as standard colour. RAL colours on request.

#### Wiring

Power input cable OPEN END 500mm



## Ordering Information

example: 1915W10(220V).0005.2780.01

1915W10(220V) · [ ] · [ ] · [ ] + [ ]

product	beam angle	light colour / CCT	finish colour
ARC-SIDE 10W 1-EMISSION	<b>0005</b> 5°	<b>2780</b> 2700K RA80	<b>01</b> stainless steel
	<b>0015</b> 15°	<b>3080</b> 3000K RA80	
	<b>0030</b> 30°	<b>4080</b> 4000K RA80	
	<b>0060</b> 60°		