

PRODUCT DATASHEET

Last information update: May 2023



DELTA

0819W300

Architectural LED floodlight for outdoor applications

Technical Features

Power	300W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	13,500 lm ±10%
Light distribution type	symmetrical / elliptical
Beam angle	9°, 15°, 20°, 30°, 45° / 15°x60°
Light colour / CCT	RGBW
CRI	-
Source type	LED (4-IN-1)
LED number	48
MacAdam step	-
Power supply	Built-in
Control	DMX512
Protection index	IP66
Impact resistance	IK08
Lifetime	50,000 hours Ta=25°C



Construction

Fluorocarbon painted die-cast aluminum body, tempered glass cover, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation

Surface mounted with adjustable bracket.

Finish Colours






RAL9023 as standard colour, other RAL colours on request.

Wiring

Power input cable OPEN END 500mm
 DMX input cable MALE connector 500mm
 DMX output cable FEMALE connector 500mm



Optional Accessories

	<p>anti-glare accessory for improved visual comfort *can not be ordered separately</p>	<p>honeycomb</p>	
	<p>anti-glare accessory for improved visual comfort *can not be ordered separately</p>		<p>visor</p>
	<p>with female 4-pin waterproof connector for DMX * specify cable length to complete order</p>	<p>leader cable</p>	
	<p>with male and female 4-pin waterproof connector for DMX * specify cable length to complete order</p>	<p>extension cable</p>	

Ordering Information

example: 0819W300.0009.4130K.01+A1

0819W300 · [] · [] · [] + []

product	beam angle	light colour / CCT	finish colour	accessory
DELTA 300W	0009 9°	4130K RGB+3000K	01 RAL9023	A1 honeycomb
	0015 15°	4140K RGB+4000K		A2 visor
	0020 20°			LC4 leader cable
	0030 30°			EC4 extension cable
	0045 45°			
	1560 15°x60°			