

## PRODUCT DATASHEET

Last information update: May 2023




### GOCCIA

1916W150

On-ground LED floodlight for outdoor applications

#### Technical Features

Power	150W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	6,750 lm ±10%
Light distribution type	symmetrical / elliptical
Beam angle	15°, 20°, 30° / 15°x60°
Light colour / CCT	RGBW
CRI	-
Source type	LED ( 4-IN-1)
LED number	24
MacAdam step	-
Power supply	Built-in
Control	DMX512
Protection index	IP66
Impact resistance	IK08
Lifetime	50,000 hours Ta=25°C



#### Construction

Fluorocarbon painted die-cast aluminum body, tempered glass cover, polycarbonate optical lenses.

#### Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

#### Installation


Surface mounted with adjustable base.

#### Finish Colours


RAL9023 as standard colour, other RAL colours on request.

#### Wiring

Power input cable OPEN END 500mm  
DMX input cable MALE connector 500mm  
DMX output cable FEMALE connector 500mm




### Optional Accessories




anti-glare accessory for improved visual comfort  
\*can not be ordered separately

honeycomb




anti-glare accessory for improved visual comfort  
\*can not be ordered separately

anti-glare glass



with female 4-pin waterproof connector for DMX  
\* specify cable length to complete order

leader cable



with male and female 4-pin waterproof connector for DMX  
\* specify cable length to complete order

extension cable

### Ordering Information

example: 1916W150.0015.4130K.01+A1

1916W150 · [ ] · [ ] · [ ] + [ ]

product	beam angle	light colour / CCT	finish colour	accessory
GOCCIA 150W	<b>0015</b> 15°	<b>4130K</b> RGB+3000K	<b>01</b> RAL9023	<b>A1</b> honeycomb
	<b>0020</b> 20°	<b>4140K</b> RGB+4000K		<b>A2</b> anti-glare glass
	<b>0030</b> 30°			<b>LC4</b> leader cable
	<b>1560</b> 15°x60°			<b>EC4</b> extension cable