

## PRODUCT DATASHEET

Last information update: May 2023




## SONAX

1914W60

Inground LED luminaire for outdoor applications

### Technical Features

Power	60W
Input voltage	DC24V ( constant voltage )
Insulation class	III
Delivered flux	2,400 lm ±10%
Light distribution type	symmetrical / elliptical
Beam angle	8°, 15°, 20°, 30° / 15°x60°
Light colour / CCT	RGBW
CRI	-
Source type	LED ( 4-IN-1 )
LED number	6
MacAdam step	-
Power supply	Not included
Control	DMX512
Protection index	IP67
Impact resistance	IK10
Walk over	yes
Drive over	yes
Lifetime	50,000 hours Ta=25°C



### Construction

Aluminum body and recessed box, tempered glass cover, stainless steel trim, polycarbonate optical lenses.

### Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

### Installation

Ground recessed with recessed box.

### Finish Colours


Stainless steel ( for trim ) as standard colour. RAL colours on request.

### Wiring

Power input cable OPEN END 500mm  
 DMX input cable MALE connector 500mm  
 DMX output cable FEMALE connector 500mm




## Optional Accessories




accessory for improved safety  
\*can not be ordered separately

anti-slip glass



with female 4-pin waterproof connector for DMX  
\* specify cable length to complete order

leader cable



with male and female 4-pin waterproof connector for DMX  
\* specify cable length to complete order

extension cable

## Ordering Information

example: 1914W60.0008.4130K.01+A1

1914W60 · [ ] · [ ] · [ ] + [ ]

product	beam angle	light colour / CCT	finish colour	accessory
SONAX 60W	<b>0008</b> 8°	<b>4130K</b> RGB+3000K	<b>01</b> stainless steel	<b>A1</b> anti-slip glass
	<b>0015</b> 15°	<b>4140K</b> RGB+4000K		<b>LC4</b> leader cable
	<b>0020</b> 20°			<b>EC4</b> extension cable
	<b>0030</b> 30°			
	<b>1560</b> 15°x60°			

## PRODUCT DATASHEET

Last information update: May 2023




### SONAX

1914W60(220V)

Inground LED luminaire for outdoor applications

#### Technical Features

Power	60W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	2,400 lm ±10%
Light distribution type	symmetrical / elliptical
Beam angle	8°, 15°, 20°, 30° / 15°x60°
Light colour / CCT	RGBW
CRI	-
Source type	LED ( 4-IN-1)
LED number	6
MacAdam step	-
Power supply	built-in
Control	DMX512
Protection index	IP67
Impact resistance	IK10
Walk over	yes
Drive over	yes
Lifetime	50,000 hours Ta=25°C



#### Construction

Aluminum body and recessed box, tempered glass cover, stainless steel trim, polycarbonate optical lenses.

#### Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

#### Installation


Ground recessed with recessed box.

#### Finish Colours

Stainless steel ( for trim ) as standard colour. RAL colours on request.

#### Wiring

Power input cable OPEN END 500mm  
 DMX input cable MALE connector 500mm  
 DMX output cable FEMALE connector 500mm



## Optional Accessories



accessory for improved safety  
\*can not be ordered separately

anti-slip glass



with female 4-pin waterproof connector for DMX  
\* specify cable length to complete order

leader cable



with male and female 4-pin waterproof connector for DMX  
\* specify cable length to complete order

extension cable

## Ordering Information

example: 1914W60(220V).0008.4130K.01+A1

1914W60(220V) · [ ] · [ ] · [ ] + [ ]

product	beam angle	light colour / CCT	finish colour	accessory
SONAX 60W	<b>0008</b> 8°	<b>4130K</b> RGB+3000K	<b>01</b> stainless steel	<b>A1</b> anti-slip glass
	<b>0015</b> 15°	<b>4140K</b> RGB+4000K		<b>LC4</b> leader cable
	<b>0020</b> 20°			<b>EC4</b> extension cable
	<b>0030</b> 30°			
	<b>1560</b> 15°x60°			