


PRODUCT DATASHEET

Last information update: Feb. 2025



CUBE MINI

0814W3

Architectural LED floodlight for outdoor applications

Technical Features

Power	3W
Input voltage	DC24V (constant voltage)
Insulation class	III
Delivered flux	240 lm ±10%
Light distribution type	Symmetrical / elliptical
Beam angle	20°, 30°, 45°, 60° / 25°x45°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	1
MacAdam step	5
Power supply	Not included
Control	ON/OFF
Protection index	IP66
Impact resistance	IK08
Lifetime	50,000 hours Ta=25°C

Construction

High weather-resistant fluorocarbon painted die-cast aluminum body, tempered glass cover, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation

Surface mounted with adjustable bracket (standard).

Finish Colours


RAL9023 Pearl Dark Grey (standard). Other RAL colours on request.

Wiring

Power input cable OPEN END 1,000 mm




Optional Accessories




honeycomb louvre
*can not be ordered separately

A02




anti-glare visor
*can not be ordered separately



A06




spike
*can not be ordered separately



A16



clamp
*can not be ordered separately



A17

Ordering Information

example: 0814W3.0020.2780.01+A02

0814W3 · [] · [] · [] + []

product	beam angle		light colour / CCT		finish colour		accessory	
CUBE MINI 3W	0020	20°	2780	2700K RA80	01	RAL9023	A02	honeycomb louvre
	0030	30°	3080	3000K RA80			A06	anti-glare visor
	0045	45°	4080	4000K RA80			A16	spike
	0060	60°					A17	clamp
	2545	25°x45°						