

PRODUCT DATASHEET

Last information update: Mar. 2025



DELTA-12

Linear LED wallwasher for outdoor applications

0819W80

Technical Features

Power	80W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	4,000 lm ±10%
Light distribution type	Symmetrical
Beam angle	Ultra spot 3°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	12
MacAdam step	5
Power supply	Built-in
Control	ON/OFF
Protection index	IP66
Impact resistance	IK08
Lifetime	50,000 hours Ta=25°C



Construction

High weather-resistant fluorocarbon painted extruded aluminum body, tempered glass cover, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation

Surface mounted with adjustable bracket (standard).

Finish Colours



RAL9023 Pearl Dark Grey (standard). Other RAL colours on request.

Wiring

Power input cable OPEN END 1,000 mm



Optional Accessories

	honeycomb louvre *can not be ordered separately	A02
	anti-glare visor *can not be ordered separately	120 231  A06

Ordering Information

example: 0819W80.0003.2780.01+A02

0819W80 · · · +

product	beam angle	light colour / CCT	finish colour	accessory
DELTA-12-80W ultra spot	00033°	27802700K RA80	01RAL9023	A02honeycomb louvre
		30803000K RA80		A06anti-glare visor
		40804000K RA80		