

PRODUCT DATASHEET

Last information update: Mar. 2025




HIGHLAND-36

0821W150

Architectural LED floodlight for outdoor applications

Technical Features

Power	150W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	12,000 lm ±10%
Light distribution type	Symmetrical / elliptical
Beam angle	6°, 12°, 20°, 30°, 45°, 60° / 10°x70°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	36
MacAdam step	5
Power supply	Built-in
Control	ON/OFF
Protection index	IP66
Impact resistance	IK08
Lifetime	50,000 hours Ta=25°C



Construction

High weather-resistant fluorocarbon painted die-cast aluminum body, tempered glass cover, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation


Surface mounted with adjustable bracket (standard).

Finish Colours


RAL9023 Pearl Dark Grey (standard). Other RAL colours on request.

Wiring

Power input cable OPEN END 1,000 mm




Optional Accessories




honeycomb louvre
*can not be ordered separately

A02



anti-glare visor
*can not be ordered separately



A06

Ordering Information

example: **0821W150.0006.2780.01+A02**

0821W150 · [] · [] · [] + []

product	beam angle	light colour / CCT	finish colour	accessory
HIGHLAND-36-150W	0006 6°	2780 2700K RA80	01 RAL9023	A02 honeycomb louvre
	0012 12°	3080 3000K RA80		A06 anti-glare visor
	0020 20°	4080 4000K RA80		
	0030 30°			
	0045 45°			
	0060 60°			
	1070 10°x70°			