

PRODUCT DATASHEET

Last information update: Jun. 2025




KISA 1000MM

LED bollard light for outdoor applications

BL06

Technical Features

Power	10W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	800 lm ±10%
Light distribution type	Asymmetrical
Light colour / CCT	3000K
CRI	80
Source type	LED
LED number	1
MacAdam step	5
Power supply	Built-in
Control	ON/OFF
Protection index	IP65
Impact resistance	IK08
Lifetime	50,000 hours Ta=25°C



Construction

High weather-resistant powder painted aluminum body, PC optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation

Surface mounted with base.

Finish Colours

4 standard colours. Other RAL colours on request.

Wiring

Power input cable OPEN END 200 mm



Optional Accessories



anchor bolts
material: galvanised steel

B01

Ordering Information

example: BL06.101000WA+B01

BL06 · +

product		power		height		finish colour		accessory	
BL06	10	10W		1000	1000MM	WA	RAL9006	B01	ANCHOR BOLTS
						JB	RAL9005		
						AG	RAL7016		
						TG	RAL7043		