


PRODUCT DATASHEET

Last information update: Mar. 2025



SONAX MINI

1920W0.5

In-ground LED uplighter for outdoor applications

Technical Features

Power	0.5W
Input voltage	DC24V (constant voltage)
Insulation class	III
Delivered flux	40 lm ±10%
Light distribution type	Symmetrical
Beam angle	120°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	1
MacAdam step	5
Power supply	Not included
Control	ON/OFF
Protection index	IP67
Impact resistance	IK10
Lifetime	50,000 hours Ta=25°C

Construction

Stainless steel body, stainless steel trim, tempered glass cover, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation

Ground recessed with clips (standard).

Finish Colours


Trim in Stainless Steel (standard). Other RAL colours on request.

Wiring

Power input cable OPEN END 1,000 mm



Optional Accessories



frosted glass
*can not be ordered separately

A05

Ordering Information

example: 1920W0.5.0120.2780.01+A05

1920W0.5 · [] · [] · [] + []

product	beam angle		light colour / CCT		finish colour		accessory
SONAX MINI 0.5W	0120	120°	2780	2700K RA80	01	stainless steel	A05 frosted glass
			3080	3000K RA80			
			4080	4000K RA80			