


PRODUCT DATASHEET

Last information update: Mar. 2025



SONAX MINI

1920W1.5

In-ground LED uplighter for outdoor applications

Technical Features

Power	1.5W
Input voltage	DC24V (constant voltage)
Insulation class	III
Delivered flux	120 lm ±10%
Light distribution type	Symmetrical
Beam angle	12°, 20°, 30°, 45°, 120°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	1
MacAdam step	5
Power supply	Not included
Control	ON/OFF
Protection index	IP67
Impact resistance	IK10
Lifetime	50,000 hours Ta=25°C

Construction

Stainless steel body, stainless steel trim, tempered glass cover, polycarbonate optical lenses, plastic recessed box.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation

Ground recessed with recessed box (standard).

Finish Colours


Trim in Stainless Steel (standard). Other RAL colours on request.

Wiring

Power input cable OPEN END 1,000 mm




Optional Accessories



honeycomb louvre
*can not be ordered separately

A02



frosted glass
*can not be ordered separately

A05

Ordering Information

example: 1920W1.5.0012.2780.01+A02

1920W1.5 · · · +

product	beam angle		light colour / CCT		finish colour		accessory	
SONAX MINI 1.5W	0012	12°	2780	2700K RA80	01	stainless steel	A02	honeycomb louvre
	0020	20°	3080	3000K RA80			A05	frosted glass
	0030	30°	4080	4000K RA80				
	0045	45°						
	0120	120°						